



Active photocatalytic air cleaners

**Alfred T. Hodgson, Hugo Destaillats,
William J. Fisk**

Lawrence Berkeley National Laboratory
Environmental Energy Technologies Division
Indoor Environment Department

Berkeley, June 29th 2007



Indoor air cleaning technologies

UV photocatalytic oxidation (UVPCO)

Outdoor or recirculated
indoor air with VOCs

UVPCO

“Clean” air with
lower VOCs





Goals of our study: performance evaluation of UVPCO

Main questions:

Can we eliminate airborne pollutants from indoor air?

Are air cleaning technologies energy-efficient and safe?

How do we define performance?

Removal efficiency of target pollutants


Formation of undesired oxidation byproducts

Catalyst inactivation



UVPCO reactor schematics

In-duct, single pass, plug-flow reactor



UV irradiation: 254 nm, 5 Watts/lamp

Flow range: 150-600 m³/h

Max pressure drop: 35 Pa

Total VOC concentration: 54-780 ppb

Face velocity: 0.5-1.8 m/s



Residence time: 0.03-0.1 s


Temperature: 20-25 °C

Relative humidity: 42-65 %



Honeycomb monolith







Realistic VOC mixtures

① 28 VOCs typical of office buildings

OB



② Mixture of common cleaning products

CP



$\text{CH}_3-\overset{\text{OH}}{\underset{\text{H}}{\text{CH}_2}}$ Alcohols	
	 Alkanes
 Terpenes	 Aromatics
	 Halogenated VOCs

 Terpenes	 Terpenoids
	 Alcohols
	 Aromatics



Realistic VOC mixtures

① 28 VOCs typical of office buildings

OB

Ethanol
Isopropanol

1-Butanol

Phenol

Ethylhexanol

Toluene
m-Xylene
1,2,4-Trimethylbenzene

n-Nonane
n-Decane
n-Undecane
n-Dodecane

Acetone
2-Butanone
MIBK
Hexanal

TCE
PCE

DCM

CS₂ Trichlorofluoromethane (R-11)
MTBE 1,1,1-Trichloroethane
 1,2-Dichlorobenzene

2-Butoxyethanol

Limonene

Decamethylcyclopentasiloxane (D₅)

② Mixture of common cleaning products

CP

Isopropanol

2-Butoxyethanol



α- Pinene
Limonene
Camphene
γ-Terpinene
Terpinolene

γ-Terpineol
α-Terpineol

p-Cymene





Office building (OB) mixture







OB mixture: oxidation products







Cleaning products (CP) mixture:







CP mixture: oxidation products






Influence of residence time on conversion efficiency

k_x : reaction rate of individual analyte x




$$CE_x = 1 - \exp(-k_x \tau)$$




TiO_2 surface @ 40-60 % RH

$$K_{ads}$$



bulk water

$$K_x^H$$




experimental
model

$$\log (k_x) = a + b \log (K_x^H) + c \log (k_x^{OH})$$




Is there competition between VOCs for TiO₂ active sites?





Byproduct formation: formaldehyde






Performance of UVPCO

- Removal efficiency of target pollutants
- Formation of undesired oxidation byproducts
- Catalyst inactivation

Example: mineralization of ethanol





Summary

- Good single pass conversion efficiencies for nearly all VOCs > 20%; in some cases as high as 80%
- Formation of unwanted byproducts (aldehydes); can be fundamentally attributed to oxidation of certain alcohols, ketones and terpenes.
- Henry's law constant is good correlation parameter to predict reaction rate of individual pollutants
- At concentrations typical of buildings (low ppb range), there is no competition between VOCs for active TiO₂ sites




Questions for discussion: How to define and evaluate the performance of passive PCO ?


- Which are the most critical target pollutants?
- Is TiO₂ (anatase) the most appropriate photocatalyst for those target pollutants?
- Should we be concerned about secondary product formation?
- Evaluation of long-term inactivation of catalyst. Regeneration?
- Effect of relative humidity on catalyst performance
- Cost analysis



Raw data: office building in Los Angeles




- Alcohols
- Aliphatic hydrocarbons
- Aldehydes
- Ketones
- Aromatic hydrocarbons
- siloxanes
- Ethylene glycols
- Glycol ethers
- Light PAHs (naphthalenes)
- Terpenoids
- Phenols
- Phthalate esters
- ... (others)...






Composite photocatalysts materials


- PICADA project (Strini et al, 2005):
 TiO_2 -containing cementitious materials:
 - cement rendering (cement + lime + sand)
 - mineral paint
- TiO_2 -pillared clays



Hectorite




TiO_2 - Hectorite






Attenuated total reflection-FTIR chamber





Attenuated total reflection-FTIR spectra





Acknowledgements

David Faulkner

Toshifumi Hotchi

Raymond Dod

Stephen O. Hay

Norberto Lemcoff

Javiera Cervini-Silva

Daria Kibanova

Funding: US Department of Energy (DOE)

Building Technologies Program


Terry Logee, Program Manager

Contract No. DE-AC02-05CH1123

Laboratory Directed Research and Development
(LDRD) program, LBNL.



Are kinetics controlled by mass-transfer?





Are kinetics controlled by the chemical step?


Langmuir - Hinshelwood

$$\frac{\partial[X]}{\partial t} \sim k\theta_X\theta_{O_2}$$


Parameters: k_x^{OH} ?

$$\theta_X = \frac{K_{ads}[X]}{(1 + K_{ads}[X])}$$

Apparent binding constant



K_{ads} depends on surface water



Demeestere et al. *Chem. Eng. Sci.* **2003**,
58, 2255-2267.

Goodman et al. *J. Phys. Chem. A* **2001**,
105, 6443-6457.



VOC removal efficiency

Fraction reacted

